Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikaflex[®]-268

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika CZ s.r.o.
		Bystrcká 1132 / 36
		62400 Brno-Komin
Telephone	:	+420 5 464 224 64
E-mail address of person	:	EHS@cz.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Toxikologické informační středisko: +420 224 91 92 93

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H317 H334

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Sikaflex[®]-268



Revision Date: 13.06.2022 Date of last issue: 18.07.2019	١	Print Date 06.12.20	
	H412	Harmful to aquatic life with long fects.	lasting ef-
Precautionary statements :	Prevention:		
·	P261 P273 P280 P284	Avoid breathing mist or vapours Avoid release to the environme Wear protective gloves. In case of inadequate ventilatio atory protection.	nt.
	Response:		
	P304 + P340	IF INHALED: Remove person to keep comfortable for breathing.	
	P342 + P311	If experiencing respiratory symp POISON CENTER/ doctor.	

Hazardous components which must be listed on the label:

4,4'-methylenediphenyl diisocyanate 2,2-bis(acryloyloxymethyl)butyl acrylate Pentamethyl piperidylsebacate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 13.06.2022
Date of last issue: 18.07.2019



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti-	>= 0,1 - < 1
2,2-bis(acryloyloxymethyl)butyl acrylate	15625-89-5 239-701-3 01-2119489896-11- XXXX	mate Acute inhalation tox- icity (dust/mist): 1,5 mg/l Aquatic Chronic 1; H410 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1;	>= 0,025 - < 0,25
		Aquatic Acute 1; H400 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

Sikaflex[®]-268

Print Date 06.12.2022

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,25
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.		
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.		
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.		
4.2 Most important symptoms and effects, both acute and delayed				
Symptoms	:	Asthmatic appearance Allergic reactions See Section 11 for more detailed information on health effects and symptoms.		
Risks	:	sensitising effects		
		May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.		



Revision Date: 13.06.2022	
Date of last issue: 18.07.2019	

Version 2.0

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

	e equipment and emergency procedures Use personal protective equipment. Deny access to unprotected persons.		
6.2 Environmental precautions			
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.		
6.3 Methods and material for containment and cleaning up			
Methods for cleaning up :	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.		
6.4 Reference to other sections For personal protection see section 8.			

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).

Sikaflex[®]-268

Revision Date: 13.06.2022

Date of last issue: 18.07.2019

Version 2.0



			Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
1 1' mathulanadinhanul dijaanuanata	101 69 9	TWA		
4,4'-methylenediphenyl diisocyanate	101-68-8		0,05 mg/m3	CZ OEL
	Further information: irritating to mucous membranes (eyes, respir- atory system) respectively skin, Sensitizing substance (with phrase H317, H334)			
		STEL	0,1 mg/m3	CZ OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0



Personal protective equipment

Eye protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	:	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Appearance	: paste
Colour	: black
Odour	: odourless

Sikaflex[®]-268



Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e		losivo limits
Upper explosion limit / Up- per flammability limit	•	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup
Auto-ignition temperature	:	Not applicable
		No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
Density	:	ca. 1,27 g/cm3 (20 °C)
Relative vapour density	:	No data available

Sikaflex[®]-268

Jika ®
Print Date 06.12.2022

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data availab

10.5 Incompatible materials

Materials to avoid	:	No data available
Materials to avoid		No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

4,4'-methylenediphenyl diisocyanate:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
		Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Silvaflox® 268

Sikaflex[®]-268

Print Date 06.12.2022

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

2,2-bis(acryloyloxymethyl)butyl acrylate:

Acute oral toxicity: LD50 Oral (Rat): 3.680 - 5.000 mg/kgAcute dermal toxicity: LD50 Dermal (Rabbit): > 5.000 mg/kg

Pentamethyl piperidylsebacate:

Acute oral toxicity : LD50 Oral (Rat): 3.230 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0



SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2-bis(acryloyloxymethyl)butyl acrylate:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 0,87 mg/l Exposure time: 96 h Method: OECD Test Guideline 203		
M-Factor (Acute aquatic tox- icity)	:	1		
M-Factor (Chronic aquatic toxicity)	:	1		
Pentamethyl piperidylsebacate:				
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h		
M-Factor (Acute aquatic tox-	:	1		

1

M-Factor (Chronic aquatic	:
toxicity)	

12.2 Persistence and degradability

No data available

icity)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

Jika ®
Print Date 06.12.2022

Revision Date: 13.06.2022	Version 2.0
Date of last issue: 18.07.2019	

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	his material and its containe ay. spose of surplus and non-re aste disposal contractor. sposal of this product, solut all times comply with the re otection and waste disposa cal authority requirements.	y retain some product residues. must be disposed of in a safe cyclable products via a licensed ons and any by-products should quirements of environmental legislation and any regional erial and runoff and contact with
European Waste Catalogue	8 04 09* waste adhesives a lvents or other dangerous s	nd sealants containing organic ubstances
Contaminated packaging	5 01 10* packaging containi v dangerous substances	g residues of or contaminated

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		

Sikaflex®-268

Jika ®
Print Date 06.12.2022

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

ADR	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
ΙΑΤΑ	: Not regulated as a dangerous good
14.4 Packing group	
ADR	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA (Cargo)	: Not regulated as a dangerous good
IATA (Passenger)	: Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- ed:
ate C9- n
d

Print Date 06.12.2022

Revision Date: 13.06.2022 Date of last issue: 18.07.2019 Version 2.0

Regulation (EC) No 649/2012 of the European Parlia- : Not applicable ment and the Council concerning the export and import of dangerous chemicals

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Not applicable

Volatile organic compounds :	:	Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties
		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

Other regulations:

Regulation of the European Parliament and Council Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) Regulation of the European Parliament and Council Regulation (EC) No 286/2011 amending, for the purposes of its adaptation to technical progress, Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP) Act No. 350/2011 Sb. on chemical substances and chemical mixtures, as amended Act No. 258/2000 Sb. the protection of public health, as amended Act No. 262/2006 Sb. The Labour Code, as amended Law No. 201/2012 Sb. On air protection, as amended Act No. 254/2001 Sb. Water, as amended Government Regulation No. 361/2007 Sb. Laying down the conditions of health of workers at work. as amended Act No. 541/2020 on waste

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H315 H317 H319	:	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.
----------------------	---	---

Sikaflex[®]-268



sion Date: 13.06.2022 of last issue: 18.07.2019	Version 2.0	Print Date 06.12.202
H332	: Harmful if inhaled.	
H334	 May cause allergy or asthma symptotics if inhaled. 	oms or breathing difficul-
H335	: May cause respiratory irritation.	
1351	: Suspected of causing cancer.	
H361f	: Suspected of damaging fertility.	
H373	 May cause damage to organs throug exposure if inhaled. 	gh prolonged or repeated
H400	: Very toxic to aquatic life.	
H410	: Very toxic to aquatic life with long las	sting effects.
Full text of other abbreviat	ons	
Acute Tox.	: Acute toxicity	
Aquatic Acute	: Short-term (acute) aquatic hazard	
Aquatic Chronic	: Long-term (chronic) aquatic hazard	
Carc.	: Carcinogenicity	
Eye Irrit.	: Eye irritation	
Repr.	: Reproductive toxicity	
Resp. Sens.	: Respiratory sensitisation	
Skin Irrit.	: Skin irritation	
Skin Sens.	: Skin sensitisation	
STOT RE	: Specific target organ toxicity - repea	ted exposure
STOT SE	: Specific target organ toxicity - single	
CZ OEL	: Czech Republic. Chemical agents at	
	cupational exposure limits	
CZ OEL / TWA	: Time weighted average	
CZ OEL / STEL	: Maximum permissible concentration	
ADR	: European Agreement concerning the Dangerous Goods by Road	e International Carriage of
CAS	: Chemical Abstracts Service	
DNEL	: Derived no-effect level	
EC50	: Half maximal effective concentration	1
GHS	: Globally Harmonized System	
ΙΑΤΑ	: International Air Transport Association	on
IMDG	: International Maritime Code for Dang	
LD50	: Median lethal dosis (the amount of a	
	once, which causes the death of 50% test animals)	
LC50	: Median lethal concentration (concen	trations of the chemical in
2030	air that kills 50% of the test animals	
		during the observation
	period)	
MARPOL	: International Convention for the Prev Ships, 1973 as modified by the Proto	
OEL	: Occupational Exposure Limit	
PBT		
	: Persistent, bioaccumulative and toxi	C
PNEC	: Predicted no effect concentration	- Francisco Devlices ant
REACH	: Regulation (EC) No 1907/2006 of the and of the Council of 18 December 2 istration, Evaluation, Authorisation a	2006 concerning the Reg-
	cals (REACH), establishing a Europe	
SVHC vPvB		ean Chemicals Agency

Print Date 06.12.2022

Revision Date: 13.06.2022				
Date of last issue: 18.07.2019				

Version 2.0

Further information					
Classification of the mixture:		Classification procedure:			
Resp. Sens. 1	H334	Calculation method			
Skin Sens. 1	H317	Calculation method			
Aquatic Chronic 3	H412	Calculation method			

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

CZ / EN