

Sikafloor® QuartzTop-100

DECLARATION OF PERFORMANCE

No. 69683487

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	69683487
2	INTENDED USE/S	Cementitious screed material for use internally in buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 4
5a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	1020

69683487 2024.02 , ver. 1 1708

6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification	
Reaction to fire	Class A1fl	System 4		
Release of corrosive substances Water permeability Water vapour permeability Compressive strength	СТ	System 4		
	NPD	System 4	EN 13813:2002	
	NPD	System 4		
	C60	System 4		
Flexural strength	F7	System 4		
Wear resistance	A6	System 4		
Sound insulation	NPD	System 4		
Sound absorption	NPD	System 4		
Thermal resistance	NPD	System 4		
Chemical resistance	NPD	System 4		

7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner Function: QMS+EHS Manager At Brno on 22 February 2024 Name: Ing. Andrej Šišolák

Function: General Manager Sika CZ, s.r.o.

At Brno on 22 February 2024

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance



2/3



13

Cilca Camilaga	AC 7	n. Switzerland
DIKA DELVICES	AG. / UHG	i. Swiizenand

DoP No. 69683487

EN 13813:2002

Notified Body 1020

Cementitious screed material for use internally in buildings

Reaction to fire	Class A1fl	
Release of corrosive substances	СТ	
Compressive strength	C60	
Flexural strength	F7	
Wear resistance	A6	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG Tüffenwies 16 8064 Zürich Switzerland www.sika.com MBCC Sika CZ s.r.o. K Májovu 1244 537 01 Chrudim Sika CZ, s.r.o. Bystrcká 1132/36 624 00 Brno Česká republika www.sika.cz

