

# SikaEmaco® N 305 FC grey

## DECLARATION OF PERFORMANCE

No. 64892205

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	64892205
2	INTENDED USE/S	Fine levelling repair mortar for concrete and reinforced concrete structures; Methods 3.1/3.2/7.1/7.2
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	SYSTEM/S OF AVCP:	System 2+
5a	HARMONISED STANDARD:	1504-3:2005
-	Notified body/ies:	1020 , 1391

64892205 2024.02 , ver. 1 1708

### 6 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1/A1fl	System 3	
Compressive strength	Class R2	System 2+	
Chloride ion content	≤ 0,05 %	System 2+	
Adhesive bond	≥ 0,8 MPa	System 2+	
Restrained shrinkage/expansion	NPD	System 2+	
Carbonation resistance	NPD	System 2+	
Elastic modulus	NPD	System 2+	
Thermal compatibility, Part 1: Freeze-thaw	≥ 0,8 MPa	System 2+	
Skid resistance	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Capillary absorption	≤ 0,5 kg/(m2·h0,5)	System 2+	<u> </u>
Dangerous substances	Comply with 5.4 EN 1504-3	System 2+	

### 7 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner Function: QMS+EHS Manager At Brno on 20 February 2024 Name: Ing. Andrej Šišolák

Function: General Manager Sika CZ, s.r.o.

At Brno on 20 February 2024

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance



CE				
23				
Sika Services AG, Zurich, Switzerland				
DoP No. 64892205				
1504-3:2005				
Notified Body 1020, 1391				
Fine levelling repair mortar for concrete and reinforced concrete structures; Methods 3.1/3.2/7.1/7.2				
Reaction to fire	Class A1/A1fl			
Compressive strength	Class R2			
Chloride ion content	≤ 0,05 %			
Adhesive bond	≥ 0,8 MPa			
Thermal compatibility, Part 1: Freeze-thaw	≥ 0,8 MPa			
Capillary absorption	≤ 0,5 kg/(m2·h0,5)			

#### http://dop.sika.com

EN 1504-3

Comply with 5.4

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

### **LEGAL NOTE**

Dangerous substances

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.



Sika Services AG Tüffenwies 16 8064 Zürich Switzerland www.sika.com MBCC Sika CZ s.r.o. K Májovu 1244 537 01 Chrudim

**Sika CZ, s.r.o.** Bystrcká 1132/36 624 00 Brno Česká republika www.sika.cz

**Declaration of Performance** 

SikaEmaco® N 305 FC grey 64892205 2024.02 , ver. 1 1708

