

SikaScreed-100

DECLARATION OF PERFORMANCE

No. 24895162

1	UNIQUE IDENTIFICATION of the product-type:	24895162
2	INTENDED USE or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Screed material and floor screeds - corresponding to the basic performance requirements of EN 13813:2002: CT-C40-F6.
3	MANUFACTURER	Sika Services AG Tüffenwies 16-22
	registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	8064 Zürich
4	AVCP System or systems of assessment and verification of constancy of performace (AVCP) or the construction product as set out in CPR, Annex V:	System 4
5	HARMONISED STANDARDS	EN 13813: 2002
6	NOTIFIED BODY In case of the declaration of performance (DoP)concerning a construction product covered by a harmonised standard:	No Notified Body required. The producer set up the factory production control of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of the factory production control.

Declaration of Performance SikaScreed-100 01/2021, Version no. 02

Identification nr. 24895162



7 DECLARED PERFORMANCE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Release of dangerous substances	СТ	-	
Water permeability	NPD	EN 1062-3	
Water vapour permeability	NPD	EN 12086	
Compressive strength	C40	EN 13892-2	
Flexural strength	F6	EN 13892-2	
Wear resistance – BCA determination	NPD	EN 13892-4	EN 13813:2002
Bond strength	NPD	EN 13892-8	
Sound insulation	NPD	EN 140-6	
Sound absorption	NPD	EN 12354-6	
Thermal resistance	NPD	EN 12664	
Chemical resistance	NPD	EN 13529	
Reaction to fire	A1 _{fl}	EN 13501	

NPD – no performance determinated

8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner Position: Quality and EHS Manager

Brno, 27.01.2021

Name: Ing. Andrej Šišolák

Position: General Manager SIKA CZ, s.r.o.

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
SikaScreed-100	EN 13813:2002	02 13 04 03 100 0 000034 1180

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

SikaScreed-100

01/2021, Version no. 02 Identification nr. 24895162

LEGAL NOTE

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Services AG, Tuffenwies 16-22, 8064 Zurich, Schweiz, plant 1180 DoP no. 24895162 EN 13813:2002

Screed material and floor screeds for interior use, class CT-C40-F6 Essential characteristics Performance Release of dangerous substances CT (cement) Compressive strength C40 Flexural strength F6 Reaction to fire A1_{fl}

http://dop.sika.com