

SikaCeram[®]-113 Classic

DECLARATION OF PERFORMANCE

no. 22926389

1	UNIQUE IDENTIFICATION of the product-type:	22926389
2	INTENDED USE or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Adhesives for tiles in the form of cementitious adhesives, normal setting, with reduced slip for walls and floors, for internal use - C1T.
3	MANUFACTURER registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AVCP System or systems of assessment and verification of constancy of performance (AVCP) or the construction product as set out in CPR, Annex V:	System 3 System 4 – reaction to fire
5	HARMONISED STANDARDS	EN 12004:2007+A1:2012
6	NOTIFIED BODY In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	1020

7 DECLARED PERFORMANCE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Euroclass A1	EN 13501-1	
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 1348:2007 – 8.2	
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$	EN 1348:2007 – 8.3	
Tensile adhesion strength after heat ageing	NPD	EN 1348:2007 – 8.4	
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	EN 1348:2007 – 8.5	EN 12004:2007 +A1:2012
Slip	$\leq 0,5 \text{ mm}$	EN 1308	
Open time: tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ after not less than 20 min.	EN 1346	
Dangerous substances	See Material Safety Data Sheet (MSDS)	NPD	

NPD – no performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.
Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner
Position: Quality and EHS Manager

Name: Ing. Andrej Šišolák
Position: General Manager SIKA CZ, s.r.o.

Brno, 01.09.2020

Brno, 01.09.2020

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance
SikaCeram®-113 Classic
01.09.2020, Version no. 01
Identification nr. 22926389
1530



20

Sika Services AG, Tüffenwies 16-22, 8064 Zürich

DoP no.: 22926389

EN 12004:2007+A1:2012

Notified Body no. 1020

Adhesives for tiles in the form of cementitious adhesives, normal setting, with reduced slip for walls and floors, for internal use - C1T.

Essential characteristics	Performance
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$
Slip	$\leq 0,5 \text{ mm}$
Open time: tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$ after not less than 20 min.
Reaction to fire	Euroclass A1

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For more information contact:

Sika CZ, s.r.o., Bystrcká 1132/36, CZ 624 00 Brno

tel: +420 546 422 464

Fax: +420 546 422 400

E-mail: sika@cz.sika.com

Declaration of Performance

SikaCeram®-113 Classic

01.09.2020, Version no. 01

Identification nr. 22926389

1530