

---

# SikaWall®-6900 Si&Si Top F-1,5

---

## DECLARATION OF PERFORMANCE

### No. 44243926

---

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	44243926
2	<b>INTENDED USE/S</b>	Factory-made organic renders for internal and external use on walls, ceilings, columns and partitions.
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16 8064 Zürich, Switzerland
5	<b>SYSTEM/S OF AVCP:</b>	System 3
6a	<b>HARMONISED STANDARD:</b>	15824-2:2017
	Notified body/ies:	1020, 1390

---

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	A2 - s1,d0	System 3	15824:2017
Water vapour permeability	V <sub>1</sub>	System 3	
Liquid water permeability	W <sub>2</sub>	System 3	
Adhesion	≥ 0.3 MPa	System 3	
Thermal conductivity ( $\lambda_{10,dry}$ ) (table value, P=50%)	0.82 W/(m·K)	System 3	
Dangerous substances	Pass, see Safety Data Sheet	System 3	

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name: Ing. Jaroslav Leischner  
Function: Product documentation specialist  
At Brno on 10.03.2026

---

Name: Ing. Martin Polák  
Function: General Manager Sika CZ, s.r.o.  
At Brno on 10.03.2026

*Leischner*

.....

.....

---

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance.



26

Sika CZ, s.r.o., Bystrcká 1132/36, 624 00 Brno

44243926

Reaction to fire	A2 - s1,d0
Water vapour permeability	V <sub>1</sub>
Liquid water permeability	W <sub>2</sub>
Adhesion	≥ 0.3 MPa
Thermal conductivity ( $\lambda_{10,dry}$ ) (table value, P=50%)	0.82 W/(m·K)
Dangerous substances	Pass, see Safety Data Sheet

EN 15824:2017

1020, 1390

Factory-made organic renders for internal and external use on walls, ceilings, columns and partitions.

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

**Sika Services AG**  
Tüffenwies 16  
8064 Zürich  
Switzerland  
[www.sika.com](http://www.sika.com)

**Sika CZ s.r.o.**  
K Májovu 1244  
537 01 Chrudim

**Sika CZ, s.r.o.**  
Bystrcká 1132/36  
624 00 Brno  
Česká republika  
[www.sika.cz](http://www.sika.cz)

### Declaration of Performance

SikaWall®-6900 Si&Si Top F-1,5  
44243926  
2026.03 , ver. 1  
1708