

**BUILDING TRUST** 

# SikaWall<sup>®</sup>-110 Machine

## DECLARATION OF PERFORMANCE No. 54623154

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	54623154
2	INTENDED USE/S	Factory made rendering and plastering general purpose mortar (GP) intended for use in walls, ceilings, columns and partitions
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	998-1:2016
	Notified body/ies:	Not required

Declaration of Performance SikaWall®-110 Machine 54623154 2025.02 , ver. 1 1708 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1 <sub>fl</sub>	System 4	
Compressive strength	Category CS II	System 4	
Water absorption	W <sub>c</sub> 0	System 4	
Water vapour permeability coefficient	μ ≤ 20	System 4	
Adhesion	≥ 0.20 N/mm <sup>2</sup> (FP:A)	System 4	998-1:2016
Thermal conductivity (λ <sub>10,dry</sub> ) (table value; Ρ=50%)	0.82 W/(m·K)	System 4	
Durability (against freeze-thaw)	min. 15 cycles	System 4	
Hazardous substances	Pass, see Safety Data Sheet	System 4	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner Function: Product documentation specialist	Name: Ing. Martin Polák Function: General Manager Sika CZ, s.r.o. At Brno on 25 February 2025
At Brno on 25 February 2025	
Leischne	fare)

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance.



Declaration of Performance SikaWall®-110 Machine 54623154 2025.02 , ver. 1 1708

**BUILDING TRUST** 

# **CE**

Sika Services AG, Tüffenwies 16, Zürich, Switzerland

#### 54623154

Reaction to fire	Class A1
Compressive strength	Category CS II
Water absorption	W <sub>c</sub> 0
Water vapour permeability coefficient	<i>μ</i> ≤ 20
Adhesion	≥ 0.20 N/mm <sup>2</sup> (FP:A)
Thermal conductivity ( $\lambda_{10,dry}$ ) (table value; P=50%)	0.82 W/(m·K)
Durability (against freeze-thaw)	min. 15 cycles
Hazardous substances	Pass, see Safety Data Sheet
998-1:2016	

ceilings, columns and partitions

http://dop.sika.com

### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

#### Sika Services AG Tüffenwies 16

8064 Zürich

Switzerland

www.sika.com

**Sika MBCC CZ, s.r.o.** K Májovu 1244 CZ-537 01 Chrudim Sika CZ, s.r.o. Bystrcká 1132/36 CZ-624 00 Brno www.sika.cz

Declaration of Performance SikaWall®-110 Machine 54623154 2025.02 , ver. 1 1708



**BUILDING TRUST**