
PCI Multiputz® MSP 2

DECLARATION OF PERFORMANCE

No. 45050200

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	45050200
2	INTENDED USE/S	Factory-made one coat mortar for external use (OC), intended for walls, ceilings and columns.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich, Switzerland
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	998-1:2016
	Notified body/ies:	Not required

Declaration of Performance

PCI Multiputz®MSP 2

45050200

2026.04 , ver. 3

1708

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1 _{fl}	System 4	998-1:2016
Compressive strength	Category CS II	System 4	
Water absorption	W _c 2	System 4	
Water permeability after weathering cycles	≤ 1 ml/cm ² after 48 h	System 4	
Water vapour permeability coefficient	μ ≤ 15	System 4	
Adhesion after weathering cycles	≥ 0.5 N/mm ² (FP:B)	System 4	
Thermal conductivity (λ _{10,dry}) (table value, P=50%)	0.61 W/(m·K)	System 4	
Durability (against freeze-thaw)	min. 25 cycles	System 4	
Hazardous substances	Pass, see Safety Data Sheet	System 4	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner
Function: Product documentation specialist
At Brno on 15.04.2026



Name: Ing. Martin Polák
Function: General Manager Sika CZ, s.r.o.
At Brno on 15.04.2026



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance.

Declaration of Performance

PCI Multiputz®MSP 2
45050200
2026.04 , ver. 3
1708



26

Sika Services AG, Tüffenwies 16, 8064 Zürich

45050200

Reaction to fire	Class A1
Compressive strength	Category CS II
Adhesion after weathering cycles	min. 0.5 N/mm ² (FP:B)
Water absorption	W _c 2
Water permeability after weathering cycles	≤ 1 ml/cm ² after 48 h
Water vapour permeability coefficient	μ ≤ 15
Thermal conductivity (λ _{10, dry}), (table value, P=50%)	0.61 W/(m·K)
Durability (against freeze-thaw)	min. 25 cycles
Hazardous substances	Pass, see Safety Data Sheet

Factory-made one coat mortar for external use (OC), intended for walls, ceilings and columns.

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Sika CZ, s.r.o.
K Májovu 1244
CZ-537 01 Chrudim

Sika CZ, s.r.o.
Bystrcká 1132/36
CZ-624 00 Brno
www.sika.cz

Declaration of Performance

PCI Multiputz®MSP 2
45050200
2026.04 , ver. 3
1708




CE_DoP_PCI_Multiputz MSP 2 EN 998-1_2016 45050200 en-EN_ver.3

Final Audit Report

2026-05-14

Created:	2026-05-14
By:	Veronika Klosova (klosova.veronika@cz.sika.com)
Status:	Signed
Transaction ID:	CBJCHBCAABAAqHxN_irPWDWHFKctRoqyptB95BQc-ip

"CE_DoP_PCI_Multiputz MSP 2 EN 998-1_2016 45050200 en-E N_ver.3" History

-  Document created by Veronika Klosova (klosova.veronika@cz.sika.com)
2026-05-14 - 07:01:37 GMT- IP address: 185.97.24.240
-  Document emailed to Martin Polak (polak.martin@cz.sika.com) for signature
2026-05-14 - 07:02:07 GMT
-  Email viewed by Martin Polak (polak.martin@cz.sika.com)
2026-05-14 - 08:55:09 GMT- IP address: 80.188.112.130
-  Document e-signed by Martin Polak (polak.martin@cz.sika.com)
Signature Date: 2026-05-14 - 08:56:09 GMT - Time Source: server- IP address: 80.188.112.130 - Signature appearance selected: IMAGE
-  Agreement completed.
2026-05-14 - 08:56:09 GMT