

DECLARATION OF PERFORMANCE

Sika[®]-Einpresshilfe EH-1

No.11892884

1	UNIQUE IDENTIFICATION of the product-typ:	11892884
2	INTENDED USE or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Injection aid admixture - corresponding to the basic performance requirements of EN 934-4:2009 Conforming to the Table ZA.1.
3	MANUFACTURER registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika Services AG Tuffenwies 16-22, 8064 Zurich, Schweiz
4	AVCP System or systems of assessment and verification of constancy of performance (AVCP) or the construction product as set out in CPR, Annex V:	System 2+
5	HARMONISED STANDARDS In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	EN 934-4:2009
6	NOTIFIED BODY	Notified factory production control certification body No. 1020 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 020041819.

Declaration of Performance
Sika[®]-Einpresshilfe EH-1
01.01.2020, Version no. 02
Identification nr. 11892884

7 DECLARED PERFORMANCE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Fluidity 30 minutes after mixing	≤25 s	EN 445	
Compressive strength	≥ 30 after 28 days	EN 445	EN 934-4: 2009
Water separation	≤ 2% after 3 hod	EN 445	
Volume change after 24 hours	0% ≤ S ≤ 5%	Annex B	


NPD – no performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner
Position: Quality and EHS Manager



Brno, 01.01.2020

Name: Ing. Andrej Šišolák
Position: General Manager SIKA CZ, s.r.o.



Brno, 01.01.2020

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika Einpresshilfe EH-1	EN 934-4:2009	02 03 01 01 002 0 000004 1180

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.


Declaration of Performance

Sika®-Einpresshilfe EH-1

01.01.2020, Version no. 02

Identification nr. 11892884

9 CE MARK

 18	
Sika Services AG, Zurich, Switzerland, factory 1180	
DoP No. 11892884	
EN 934-4:2009	
Notified Body 1020	
Injection aid admixture	
Essential characteristics	Performance
Fluidity 30 minutes after mixing	≤25 s
Compressive strength	≥ 30 MPa after 28 days
Water separation	≤ 2% after 3 hod
Volume change after 24 hours	0% ≤ S ≤ 5%

<http://dop.sika.com>