

# Sika ThermoCoat®-5 Mineral Top Fine

## DECLARATION OF PERFORMANCE No. 65480287

|    |  |   |
|----|--|---|
| 1  | <b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b> | 65480287  |
| 2  | <b>INTENDED USE/S</b>                                  | EN 998-1:2016<br>Factory made rendering/ plastering mortar (GP) use for finishing work on walls, pillars, partitions and ceilings according EN 998-1:2016 |
| 3  | <b>MANUFACTURER:</b>                                   | Sika CZ, s.r.o.<br>Bystrcká 1132/36<br>CZ-624 00 Brno   |
| 4  | <b>AUTHORISED REPRESENTATIVE:</b>                      | Not applicable  |
| 5  | <b>SYSTEM/S OF AVCP:</b>                               | System 4  |
| 6a | <b>HARMONISED STANDARD:</b>                            | EN 998-1:2016   |
|    | Notified body/ies:                                     | Not applicable  |

---

**7 DECLARED PERFORMANCE/S**

---

| Essential Characteristics  | Performance                   | AVCP     | Harmonised Technical Specification |
|--|-------------------------------|----------|------------------------------------|
| Compression strength   | class CS III                  | System 4 | EN 998-1:2016                      |
| Adhesive strength  | 0,30 N/mm <sup>2</sup> (FP:A) | System 4 |                                    |
| Reaction to fire   | class A1                      | System 4 |                                    |
| Water absorption   | category Wc 0                 | System 4 |                                    |
| Water vapour permeability  | μ max. 10                     | System 4 |                                    |
| Thermal conductivityt ( $\lambda_{10 \text{ dry,}}$ )<br>(table value, P=50 %) | 0,47 W/mK                     | System 4 |                                    |
| Durability   | min. 15 cycles                | System 4 |                                    |
| Release of dangerous substances  | passed, see MSDS              | System 4 |                                    |

---


**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner  
Function: Quality and EMS manager Sika CZ  
At Brno on 15<sup>th</sup> December 2019



.....

Name: Ing. Andrej Šišolák  
Function: Executive Sika CZ  
At Brno on 15<sup>th</sup> December 2019



.....

---

End of information as required by Regulation (EU) No 305/2011



19

Sika CZ, s.r.o., Bystrcká 1132/36, CZ-624 00 Brno

DoP No. 65480287

EN 998-1:2016

Factory made rendering/ plastering mortar (GP) use for finishing work on walls, pillars, partitions and ceilings

|   |                               |
|---|-------------------------------|
| Compression strength  | class CS III                  |
| Adhesive strength   | 0,30 N/mm <sup>2</sup> (FP:A) |
| Reaction to fire  | class A1                      |
| Water absorption  | category Wc 0                 |
| Water vapour permeability   | $\mu$ max. 10                 |
| Thermal conductivity ( $\lambda_{10 \text{ dry}}$ ) (table value, P=50 %) | 0,47 W/mK                     |
| Durability  | min. 15 cycles                |
| Release of dangerous substances   | Satisfies, via SDS            |

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sika Thermocoat-5 Mineral Top Fine  
65480287  
2019.12 , ver. 01  
1530, 1349