

PCI Pecicret® PR

DECLARATION OF PERFORMANCE

No. 81418558

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	81418558
2	INTENDED USE/S	Factory made general purpose masonry mortar (G) intended for use in walls, pillars and partitions
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 998-2:2016
Notified body/ies:		1020

Declaration of Performance

PCI Pecicret®PR
81418558
2025.10 , ver. 2
1708

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class A1	System 2+	998-2:2016
Compressive strength	Category M 5	System 2+	
Water absorption	Max. 0.2 kg/(m ² ·min ^{0,5})	System 2+	
Bond strength (shear strength)	0.30 N/mm ² (tab. value)	System 2+	
Water vapour permeability (table value)	μ 5/20	System 2+	
Thermal conductivity (λ _{10,dry}) (table value, P=50%)	0.45 W/(m·K)	System 2+	
Durability (freezing/thawing)	min. 25 cycles	System 2+	
Content of chlorides	≤ 0.2 %	System 2+	
Hazardous substances	Pass, see Safety Data Sheet	System 2+	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Ing. Jaroslav Leischner
Function: Product documentation specialist
At Brno on 09.10.2025



Name: Ing. Martin Polák
Function: General Manager Sika CZ, s.r.o.
At Brno 09.10.2025



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance.

Declaration of Performance

PCI Pecicret®PR
81418558
2025.10 , ver. 2
1708



25

Sika Services AG, Tüffenwies 16, Zurich, Switzerland

81418558

Reaction to fire	Class A1
Compressive strength	Category M 5
Water absorption	max. 0.8 kg/(m ² ·min ^{0.5})
Content of chlorides	≤ 0.1%
Bond strength (shear strength)	0.30 N/mm ² (tab. value)
Water vapour permeability (table value)	μ 5/20
Thermal conductivity (λ _{10,dry}) (table value, P=50%)	0.45 W/(m·K)
Durability (against freeze-thaw)	min. 25 cycles
Hazardous substances	Pass, see Safety Data Sheet

EN 998-2:2016

1020

Factory made general purpose masonry mortar (G) intended for use in walls, pillars and partitions

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Sika CZ s.r.o.
K Májovu 1244
537 01 Chrudim

Sika CZ, s.r.o.
Bystrcká 1132/36
624 00 Brno
Česká republika
www.sika.cz

Declaration of Performance

PCI Pecicret®PR
81418558
2025.10 , ver. 2
1708



Declaration of Performance

PCI Pecicret®PR

81418558

2025.10 , ver. 2

1708

