
Sikadur[®]-32+

DECLARATION OF PERFORMANCE

No. 85644331

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	85644331
2	INTENDED USE/S	EN 1504-6:2006 Anchoring products for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	0099, 0370

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Pull-out strength	Displacement $\leq 0,6$ mm at load of 75 kN	System 2+	EN 1504-6:2006
Chloride ion content	≤ 0.05 %	System 2+	
Glass transition temperature	≥ 45 °C	System 2+	
Reaction to fire	Class B _{FL} -s1 / C-s1, d0	System 3	
Durability/Creep under tensile load	$\leq 0,6$ mm at 50 kN for 3 months	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization and Approvals
At Warsaw on 19 March 2021

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 19 March 2021



End of information as required by Regulation (EU) No 305/2011



21

Sika Services AG, Zurich, Switzerland

85644331

EN 1504-6:2006

Notified Body 0099, 0370

Anchoring products for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works

Pull-out strength	Displacement \leq 0,6 mm at load of 75 kN
Chloride ion content	\leq 0.05 %
Glass transition temperature	\geq 45 °C
Reaction to fire	Class B _{FL} -s1 / C-s1, d0
Durability/Creep under tensile load	\leq 0,6 mm at 50 kN for 3 months

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikadur®-32+
85644331
2021.03 , ver. 1
1053

Template for translation. Only for
internal use

Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance

Sikadur®-32+
85644331
2021.03 , ver. 1
1053

4/4

Template for translation. Only for
internal use

BUILDING TRUST

